

Safety data sheet for AIREX® C71

According to Regulation (EC) No. 1907/2006 & GHS

Page 1 of 3

revised: January 23rd, 2017 GM--SDS-012

1. Identification of substance / preparation and of the company

> AIREX® C71 Rigid foam (C71.55, C71.75)

Core material in sandwich constructions Use of substance / preparation:

Airex AG Company identification:

> 5643 Sins. Switzerland Tel +41 41 789 66 00 Fax +41 41 789 66 60

2. Hazards identification

AIREX® C71 does not constitute any risk to public health and environment if it is used as intended.

Possible health issues:

- Harmful to health due to inhaling vapour and dust that may be produced by sawing, grinding and thermoforming.

- Harmful to health due to ingesting dust that may be produced by grinding and sawing

3. Composition / Information on ingredients

Rigid polymeric foam on the basis of Polyvinylchloride modified by an interpenetrating polymer network with aromatic amides.

Carbon dioxide (CO₂ / produced by the reaction of water with isocyanate components). Blowing agent:

Residues of chemical blowing agent. Organic colour pigments. Stabilisers. Further ingredients:

4 First aid measures

> Inhalation of processing fumes: Move victim to fresh air; obtain medical attention if irritation persists.

Move victim to fresh air and obtain medical attention. Inhalation of gases in case of fire:

Skin contact: Wash with water.

Eye contact: Flush with water if irritation develops.

Ingestion: No special measures required. Seek medical attention if symptoms develop.

5. Fire-fighting measures

> Suitable extinguishing media: Foam, water spray, extinguishing powder, carbon dioxide.

Extinguishing media which must

Direct water jet. not be used:

Hydrogen chloride (HCI) and hydrogen cyanide (HCN). Hazardous combustion products:

Use respiratory protection independent of recirculated air.

Accidental release measures

No special measures required.

7. Handling and storage

> Handling: It must be ensured that there is good ventilation and suction on the processing machines

and where dust development may occur.

Storage: Stow away from immediate and dangerous sources of ignition. Danger of electrostatic

North America I South America

charges when stored in very dry areas.





corematerials@3AComposites.com

5643 Sins, Switzerland T +41 41 789 66 00 | F +41 41 789 66 60



Safety data sheet for AIREX® C71

According to Regulation (EC) No. 1907/2006 & GHS

Page 2 of 3

revised: January 23rd, 2017 GM--SDS-012

8. Exposure control / personal protection

General protection measures

Sufficient air circulation is required during processing. The exhaust air must not be recirculated. If the workstation cannot be sufficiently ventilated, it is imperative that respiratory protection (A2P3 filter) is worn.

Workstation threshold values

Dust	Source	Value type	Value (mg/m³)	Remarks
	SUVA	MAC values	10	Inhalable particles

Gasses / Vapours	Source	Value type	Value (mg/m³)	Remarks
Tetramethylsuccinonitrile	SUVA	MAC values	3	
Methacrylnitrile	SUVA	MAC values	3	

Personal protection equipment

Respiratory protection: Effective breathing mask

Hand protection: Gloves Eye protection: Goggles

9. Physical and chemical properties

Polymer foam sheet with visible cell structure. Physical state / form:

Various, depending on density. Colour. 65 to 80 °C ISO 537 Glass transition temperature:

Decomposition temperature: > 220 °C

380 °C **ASTM D 1929** Flash ignition temperature:

50 - 100 kg/m³ ISO 845 Density:

Solubility: Insoluble in: Water, sea water, acids, alkalis, aliphatic hydrocarbons

Soluble in: Aromatic hydrocarbons, Ketones, chlorinated hydrocarbons

10. Stability and reactivity

> Stable under normal conditions General information: High temperatures (> 180 °C) Conditions to avoid:

Materials to avoid: Not applicable.

Dangerous decomposition Tetramethylsuccinonitrile (TMSN)

Methacrylnitrile products: Isobutyronitrile

Hydrogen chloride (HCI)

Hydrogen cyanide (HCN) in small amounts

Carbon dioxide (CO₂) Carbon monoxide (CO)

11. **Toxicological information**

No data available. Toxicological tests:

Experience with man:

Skin contact: Grinding dust may cause irritation to people with sensitive skin.

Eye contact: Dust may cause irritation.

Inhalation: Dust may cause irritation of respiration tract. Dizziness, nausea and headaches may occur

Ingestion: No symptoms known.





Safety data sheet for AIREX® C71

According to Regulation (EC) No. 1907/2006 & GHS Page 3 of 3 revised: January 23rd, 2017

GM--SDS-012

12. Ecological information

Ecotoxicity: The total amount of all heavy metals is < 100 mg/kg [ppm].

Mobility: Not soluble in water, therefore effects on groundwater are unlikely.

Persistence and degradability: Biologically not degradable.

13. Disposal considerations

Subject to legislation by local authorities, the product can be disposed of together with domestic refuse and industrial waste. Waste and residues can be incinerated in a plant equipped with flue gas washing, together with domestic waste.

14. Transport information

Railroad RID No restriction.

Road ADR No restriction.

Sea IMDG Code No restriction.

Air ICAO-TI/IATA-DGR No restriction.

UN-Classification Not required.

15. Regulatory information

AIREX® C71 rigid plastic foam does not require marking under the following directives or is not concerned by the following regulations:

- Europe: Directive 67/548/EWG, ("DSD"), Directive 1999/45/EC, ("DPD"), Regulation (EC) No 1272/2008 ("CLP").
- US: OSHA .29 CFR 1910.1200 and .49 CFR 171.8 (EPA 40 CFR 117) spill, leak and disposal regulations of the US Department of Transportation.
- Canada: WHMIS and TDG.

16. Other information

This issue of the safety data sheet replaces the issue released on July 22nd, 2016.

The information given in this material safety data sheet is accurate to the best of our knowledge, but without any guarantee. It is given in good faith based on the current state of knowledge and experience. It is issued in respect of safety requirements and does not purpose to provide information on the quality of the material.

